

## Straight AdBlue<sup>®</sup> Quick Connectors 9.49 x 8mm 3pc

A set of 3 straight AdBlue<sup>®</sup> fuel line quick connectors allowing for tight connections on 8mm fuel lines. Quick connectors are designed for the automotive industry for the transfer of fuel, oil, water cooling systems and air. The self locking connector enables it to be connected and disconnected with ease and speed, with the wide operating temperature range ensures it can cope with the extreme temperatures that could lead to cracking and leaks. To ease the fitting of the hard plastic fuel pipe to the connectors, use Laser Tools Pipe Connector Insertion Tool, Part No. 6933.



### Additional Information

- Straight connectors for AdBlue<sup>®</sup>, suits: 8mm nylon pipe; 7.5mm ID rubber hose.
- Constant running pressure: 7 bar (101psi); max pressure: 9 bar (130psi). Operating temperature: -40°C to 70°C.
- Body manufactured from nylon PA12; O-ring from EPDM seal. Made to SAE J2044-2009 standards.
- Red tab for AdBlue<sup>®</sup> identification (note: standard fuel connectors have grey tabs).
- Included in assorted box of straight AdBlue<sup>®</sup> quick fuel line connectors, see Connect Part No. 34227.

<http://product/34248>

